

Data sheet for SIMOTICS S-1FT7

Article No. : 1FT7132-5AF71-1BB5



Figure similar

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data

| | |
|-------------------------|--------------------------|
| Rated speed | 3,000 rpm |
| Number of poles | 8 |
| Rated torque (100 K) | 27.0 Nm |
| Rated current | 14.00 A |
| Static torque (60 K) | 75.0 Nm |
| Static torque (100 K) | 90.0 Nm |
| Stall current (60 K) | 36.00 A |
| Stall current (100 K) | 43.50 A |
| Rotor moment of inertia | 512.00 kgcm ² |
| Efficiency | 94.0 % |

Physical constants

| | |
|-----------------------------|--------------------------------|
| Torque constant | 2.08 Nm/A |
| Voltage constant at 20° C | 137.0 V/1000*min ⁻¹ |
| Winding resistance at 20° C | 0.06 Ω |
| Rotary field inductance | 2.0 mH |
| Electrical time constant | 32.00 ms |
| Mechanical time constant | 2.00 ms |
| Thermal time constant | 75 min |
| Shaft torsional stiffness | 231,000 Nm/rad |
| Net weight of the motor | 88.0 kg |

Mechanical data

| | |
|--------------------------|--|
| Motor type | Permanent-magnet synchronous motor |
| Motor type | Compact |
| Shaft height | 132 |
| Cooling | Natural cooling |
| Radial runout tolerance | 0.050 mm |
| Concentricity tolerance | 0.125 mm |
| Axial runout tolerance | 0.125 mm |
| Vibration severity grade | Grade R |
| Degree of protection | IP67 |
| Design acc. to Code I | IM B5 (compatible with 1FT6) |
| Temperature monitoring | Pt1000 temperature sensor |
| Color of the housing | Standard (pearl dark gray similar to RAL 9023) |
| Shaft end type | Fitted key and keyway |
| Sensor design | Encoder AS24DQI: Absolut encoder Singleturn 24 bit - with signal connection RJ45 |
| Electrical connection | Transverse facing to right site |
| Connector size | 3 |

Optimum operating point

| | |
|---------------|-----------|
| Optimum speed | 2,150 rpm |
| Optimum power | 12.0 kW |

Limiting data

| | |
|-----------------------------------|-----------|
| Max. permissible speed (mech.) | 3,600 rpm |
| Max. permissible speed (inverter) | 3,600 rpm |
| Maximum torque | 290.0 Nm |
| Maximum current | 172.00 A |

Recommended Motor Module

| | |
|--------------------------|----------|
| Rated inverter current | 45.00 A |
| Maximum inverter current | 85.00 A |
| Maximum torque | 168.0 Nm |

Holding brake

| | |
|------------------------|------------------------|
| Holding brake version | Permanent-magnet brake |
| Holding torque | 140.0 Nm |
| Braking torque | 60.0 Nm |
| Power supply voltage | DC 24 V |
| Coil current | 1.80 A |
| Permissible brake work | 9,800 J |
| Opening time | 350 ms |
| Closing time | 70 ms |