

## Data sheet for SIMOTICS S-1FK7

MLFB-Ordering data

1FK7064-4CC74-1SH0



Figure similar

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

### Engineering data

Rated speed (100 K)	2000 rpm
Number of poles	6
Rated torque (100 K)	10.0 Nm
Rated current	7.1 A
Static torque (60 K)	10.00 Nm
Static torque (100 K)	12.0 Nm
Stall current (60 K)	6.60 A
Stall current (100 K)	8.10 A
Moment of inertia	8.500 kgcm <sup>2</sup>
Efficiency	93.0 %

### Physical constants

Torque constant	1.48 Nm/A
Voltage constant at 20° C	94.0 V/1000*min <sup>-1</sup>
Winding resistance at 20° C	0.58 Ω
Rotating field inductance	21.5 mH
Electrical time constant	37.00 ms
Mechanical time constant	0.60 ms
Thermal time constant	55 min
Shaft torsional stiffness	22500 Nm/rad
Net weight of the motor	16.8 kg

### Mechanical data

Motor type	Permanent-magnet synchronous motor
Motor type	High Dynamic
Shaft height	63
Cooling	Natural cooling
Radial runout tolerance	0.040 mm
Concentricity tolerance	0.10 mm
Axial runout tolerance	0.10 mm
Vibration severity grade	Grade A
Connector size	1
Degree of protection	IP64
Design acc. to Code I	IM B5 (IM V1, IM V3)
Temperature monitoring	Pt1000 temperature sensor
Electrical connectors	Connectors for signals and power rotatable
Color of the housing	Standard (Anthracite RAL 7016)
Holding brake	with holding brake
Shaft extension	Plain shaft
Encoder system	Multi-pole resolver (number of pole pairs corresponds to number of pole pairs of the motor)



Figure similar

MLFB-Ordering data

1FK7064-4CC74-1SH0

### Optimum operating point

Optimum speed	2000 rpm
Optimum power	2.1 kW

### Limiting data

Max. permissible speed (mech.)	7500 rpm
Max. permissible speed (inverter)	6150 rpm
Maximum torque	32.0 Nm
Maximum current	25.0 A

### Holding brake

Holding brake version	Permanent-magnet brake
Holding torque	13.0 Nm
Power supply voltage	DC 24 V $\pm$ 10 %
Coil current	0.8 A
Opening time	100 ms
Closing time	50 ms
Highest braking work	380 J

### Recommended Motor Module

Rated inverter current	9 A
Maximum inverter current	27 A
Maximum torque	32.00 Nm