

## Data sheet for SIMOTICS S-1FK7

MLFB-Ordering data

1FK7080-2AF71-1PG2



Figure similar

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Engineering data		Mechanical data			
Rated speed (100 K)	3000 rpm	Motor type	Permanent-magnet synchronous motor		
Number of poles	8	Motor type	Compact		
Rated torque (100 K)	6.8 Nm	Shaft height	80		
Rated current	4.4 A	Cooling	Natural cooling		
Static torque (60 K)	6.60 Nm	Radial runout tolerance	0.050 mm		
Static torque (100 K)	8.0 Nm	Concentricity tolerance	0.10 mm		
Stall current (60 K)	4.00 A	Axial runout tolerance	0.10 mm		
Stall current (100 K)	4.90 A	Vibration severity grade	Grade A		
Moment of inertia	14.200 kgcm <sup>2</sup>	Connector size	1		
Efficiency	92.0 %	Degree of protection	IP65 and DE flange IP67		
<b>Physical constants</b>		Design acc. to Code I	IM B5 (IM V1, IM V3)		
		Temperature monitoring	Pt1000 temperature sensor		
		Electrical connectors	Connectors for signals and power rotatable		
		Color of the housing	Standard (Anthracite RAL 7016)		
		Holding brake	without holding brake		
		Shaft extension	Plain shaft		
		Encoder system	Resolver R14DQ: resolver 14 bits (resolution 16384, internal 2-pole)		
		Torque constant	1.61 Nm/A		
		Voltage constant at 20° C	105.0 V/1000*min <sup>-1</sup>		
		Winding resistance at 20° C	0.98 Ω		
Rotating field inductance	17.2 mH				
Electrical time constant	17.50 ms				
Mechanical time constant	1.52 ms				
Thermal time constant	40 min				
Shaft torsional stiffness	120000 Nm/rad				
Net weight of the motor	10.3 kg				



Figure similar

MLFB-Ordering data

1FK7080-2AF71-1PG2

Optimum operating point		Recommended Motor Module	
Optimum speed	3000 rpm	Rated inverter current	5 A
Optimum power	2.1 kW	Maximum inverter current	15 A
Limiting data		Maximum torque	22.10 Nm
Max. permissible speed (mech.)	6000 rpm		
Max. permissible speed (inverter)	5500 rpm		
Maximum torque	25.0 Nm		
Maximum current	18.0 A		