

SITOR fuse link, with blade contacts, NH3, In: 560 A, gR, Un AC: 690 V, Front indicator



Figure similar

Model	
product brandname	SENTRON
Product designation	SITOR fuse link
Design of the product	With blade contacts
Design of an identification indicator	front indicator
Design of the switching contact	With blade contacts, silver-plated
Design of the fuse link	SITOR, LV HRC design
General technical data	
Size of fuse system / acc. to DIN EN 60269-1	NH3
Operating class of the fuse link	gR
circuit-breaker / Design	3NE
Varying load factor (WL)	1
Switching capacity	
Switching capacity current	
<ul style="list-style-type: none"> <li>• acc. to IEC 60947-2 / rated value</li> </ul>	100 kA
Dissipation	

<b>Power loss [W]</b>	
<ul style="list-style-type: none"> <li>• for rated value of the current / at AC / in hot operating state / per pole</li> </ul>	60 W
<ul style="list-style-type: none"> <li>• maximum</li> </ul>	60 W

### Electricity

rated current I <sub>n</sub> / IEC, DIN/VDE / at 40 Cel	560 A
Current / at AC / rated value	560 A

### Product details

<b>Product description</b>	Not non-interchangeable
----------------------------	-------------------------

### Mechanical Design

<b>Mounting position</b>	Any, preferably vertical
--------------------------	--------------------------

### Environmental conditions

<b>Ambient temperature</b>	
<ul style="list-style-type: none"> <li>• minimum</li> </ul>	-20 °C
<ul style="list-style-type: none"> <li>• maximum</li> </ul>	50 °C
<b>Environmental category</b>	-20 to +50 at 95% relative humidity

### Certificates

<b>Equipment marking</b>	
<ul style="list-style-type: none"> <li>• acc. to DIN EN 61346-2</li> </ul>	F
<ul style="list-style-type: none"> <li>• acc. to DIN EN 81346-2</li> </ul>	F

<b>General Product Approval</b>	<b>other</b>
---------------------------------	--------------

[sonstig](#)



UR

### Further information

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/lowvoltage/catalogs>

**Industry Mall (Online ordering system)**

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3NE1435-2>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<http://support.automation.siemens.com/WW/view/en/3NE1435-2/all>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3NE1435-2](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NE1435-2)

**CAX-Online-Generator**

<http://www.siemens.com/cax>

**Tender specifications**

<http://www.siemens.com/specifications>

