

## Data sheet for SIMOTICS M-1PH8

Article No. : 1PH8163-1AD10-2GA2



Figure similar

Client order no. :  
Order no. :  
Offer no. :  
Remarks :

Item no. :  
Consignment no. :  
Project :

### Engineering data

		P <sub>N</sub> [kW]	M <sub>N</sub> [Nm]	I <sub>N</sub> [A]	U <sub>N</sub> [V]	f <sub>N</sub> [Hz]	n <sub>N</sub> [rpm]	M <sub>max</sub> [Nm]	I <sub>max</sub> [A]	n <sub>max</sub> [rpm]	M <sub>0</sub> [Nm]	I <sub>0</sub> [A]	η	cos φ	I <sub>μ</sub> [A]
Y	ALM 400V	25.0	208.0	55.0	343	39.2	1,150	600	151.0	6,500	248.0	61	0.915	0.880	17.5
	BLM/SLM 400V	22.0	210.0	55.0	300	34.2	1,000	600	151.0	6,500	248.0	61	0.909	0.890	17.3
	ALM 480V	31.0	197.0	52.0	442	50.9	1,500	600	151.0	6,500	248.0	61	0.930	0.880	17.7
	BLM/SLM 480V	28.0	198.0	52.0	400	45.8	1,350	600	151.0	6,500	248.0	61	0.924	0.880	17.7

### Mechanical data

Motor type	Squirrel cage asynchronous motor
Shaft height	160
Cooling	Forced ventilation NDE -> DE
Vibration severity grade	R/A
Shaft and flange accuracy	R
Degree of protection	IP55
Design acc. to Code I	IM B3 (IM V5, IM V6, IM B6, IM B7, IM B8)
Temperature monitoring	Pt1000 temperature sensor in the stator winding
Color	Standard (Anthracite RAL 7016)
Type of the bearing	Standard
Shaft end	Feather key with half key balancing
Encoder system	Without encoder

### External fan

#### Max. power consumption

3 AC 400 V / 50 Hz (±10%)	0.16 A
3 AC 400 V / 60 Hz (±10%)	0.21 A
3 AC 480 V / 60 Hz (±10%)	0.21 A

<sup>1)</sup> at a rated frequency of 4 kHz and a speed range of up to 5000 rpm

### Physical constants

Thermal time constant	35 min
Moment of inertia	2,160 kgcm <sup>2</sup>
Weight (approx.)	196 kg

### Connection

Type of electrical connection	Terminal box
Position of the connection	NDE top
Power connection	right
Signal connection	DE
Terminal box designation	gk863

### Cooling data and sound pressure level

Airflow, min.	0.16 m <sup>3</sup> /s
Sound pressure level LpA(1m) motor + external fan operation 50 HZ rated load, tolerance + 3dB	73 dB <sup>1)</sup>
Air discharge	axial
Pressure drop	200 Pa