

Data sheet for SIMOTICS M-1PH8

Article No. : 1PH8137-1HF10-2BA1



Figure similar

Client order no. :

Item no. :

Order no. :

Consignment no. :

Offer no. :

Project :

Remarks :

Engineering data

| | P_N [kW] | M_N [Nm] | I_N [A] | U_N [V] | f_N [Hz] | n_N [rpm] | M_{max} [Nm] | I_{max} [A] | n_{max} [rpm] | M_0 [Nm] | I_0 [A] | η | $\cos \phi$ | I_μ [A] | |
|---|------------------|---------------|--------------|--------------|---------------|----------------|-------------------|------------------|--------------------|---------------|--------------|--------|-------------|----------------|------|
| Y | ALM 400V | 25.0 | 136.0 | 56.0 | 353 | 59.6 | 1,750 | 380 | 151.0 | 8,000.0 | 172.0 | 68 | 0.907 | 0.84 | 23.1 |
| | BLM/SLM 400V | 22.0 | 140.0 | 56.0 | 308 | 51.3 | 1,500 | 380 | 151.0 | 8,000.0 | 172.0 | 68 | 0.904 | 0.84 | 24.2 |
| | ALM/BLM/SLM 480V | 28.0 | 134.0 | 55.0 | 401 | 67.9 | 2,000 | 380 | 151.0 | 8,000.0 | 172.0 | 68 | 0.931 | 0.84 | 23.1 |

Mechanical data

| | |
|---------------------------|---|
| Motor type | Squirrel cage asynchronous motor |
| Shaft height | 132 |
| Cooling | Forced ventilation NDE -> DE |
| Vibration severity grade | R/A |
| Shaft and flange accuracy | R |
| Degree of protection | IP55 |
| Design acc. to Code I | IM B3 (IM V5, IM V6) |
| Temperature monitoring | KTY84 temperature sensor in the stator winding |
| Color | Standard (Anthracite RAL 7016) |
| Type of the bearing | Standard with fixed bearing |
| Shaft extension | Feather key with half key balancing |
| Encoder system | Incremental encoder HTL 1024 S/R, max. encoder speed = 9000 rpm |

Physical constants

| | |
|-----------------------|------------------------|
| Thermal time constant | 30 min |
| Moment of inertia | 0.109 kgm ² |
| Weight (approx.) | 141 kg |

Connection

| | |
|-------------------------------|--------------|
| Type of electrical connection | Terminal box |
| Position of the connection | NDE top |
| Power connection | right |
| Signal connection | DE |
| Terminal box designation | gk833 |

Cooling data and sound pressure level

| | |
|--|------------------------|
| Airflow, min. | 0.09 m ³ /s |
| Sound pressure level L _{pA} (1m) motor + external fan operation 50 HZ rated load, tolerance + 3dB | 70 dB ¹⁾ |
| Air discharge | axial |
| Pressure drop | 140 Pa |

¹⁾ at a rated frequency of 4 kHz and a speed range of up to 5000 rpm