

## Data sheet for SIMOTICS S-1FK7

MLFB-Ordering data

1FK7044-7AF71-1PA0

No image available for this configuration.

Figure similar

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

### Engineering data

Rated speed (100 K)	3000 rpm
Number of poles	6
Rated torque (100 K)	3.5 Nm
Rated current	4.0 A
Static torque (60 K)	3.00 Nm
Static torque (100 K)	4.0 Nm
Stall current (60 K)	3.40 A
Stall current (100 K)	4.50 A
Moment of inertia	1.280 kgcm <sup>2</sup>
Efficiency	91.0 %

### Physical constants

Torque constant	0.86 Nm/A
Voltage constant at 20° C	57.0 V/1000*min <sup>-1</sup>
Winding resistance at 20° C	1.50 Ω
Rotating field inductance	20.0 mH
Electrical time constant	13.30 ms
Mechanical time constant	0.78 ms
Thermal time constant	45 min
Shaft torsional stiffness	9500 Nm/rad
Net weight of the motor	7.7 kg

### Mechanical data

Motor type	Permanent-magnet synchronous motor
Motor type	High Dynamic
Shaft height	48
Cooling	Natural cooling
Radial runout tolerance	0.040 mm
Concentricity tolerance	0.08 mm
Axial runout tolerance	0.08 mm
Vibration severity grade	Grade A
Connector size	1
Degree of protection	IP64
Design acc. to Code I	IM B5 (IM V1, IM V3)
Temperature monitoring	KTY84 temperature sensor in the stator winding
Electrical connectors	Connectors for signals and power rotatable
Color of the housing	without
Holding brake	without holding brake
Shaft extension	Feather key
Encoder system	Resolver R14DQ: resolver 14 bits (resolution 16384, internal 2-pole)

MLFB-Ordering data

1FK7044-7AF71-1PA0

Figure similar

Optimum operating point		Recommended Motor Module	
Optimum speed	3000 rpm	Rated inverter current	5 A
Optimum power	1.1 kW	Maximum inverter current	10 A
<b>Limiting data</b>		Maximum torque	8.80 Nm
Max. permissible speed (mech.)	8000 rpm		
Max. permissible speed (inverter)	10100 rpm		
Maximum torque	12.0 Nm		
Maximum current	14.8 A		