

Data sheet for SIMOTICS S-1FT7

MLFB-Ordering data

1FT7064-5AF70-1FB1



Figure similar

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data		Mechanical data	
Rated speed	3000 rpm	Motor type	Permanent-magnet synchronous motor
Number of poles	10	Design of the motor type	Compact
Rated torque (100 K)	7.6 Nm	Shaft height	63 mm
Rated current	5.2 A	Cooling	Natural cooling
Static torque (60 K)	7.70 Nm	Radial runout tolerance	N
Static torque (100 K)	9.0 Nm	Vibration severity grade	Grade A
Stall current (60 K)	4.9 A	Degree of protection	IP65
Stall current (100 K)	5.7 A	Design acc. to Code I	IM B5 (new flange design)
Rotor moment of inertia	0.0014700 kgm ²	Temperature monitoring	Pt1000 temperature sensor
Efficiency	93.0 %	Color of the housing	Pearl dark grey RAL 9023
Physical constants		Holding brake version	Permanent-magnet brake
Torque constant	1.57 Nm/A	Shaft end type	Fitted key and keyway
Voltage constant at 20° C	100.0 V/1000*min ⁻¹	Sensor design	Encoder AM22DQ: absolute encoder 22 bits (resolution 4194304, encoder-internal 2048 S/R) + 12 bits multi-turn (traversing range 4096 revolutions)
Winding resistance at 20° C	0.92 Ω	Electrical connectors	Connector turnable
Rotating field inductance	10.0 mH	Connector size	1
Electrical time constant	11.00 ms		
Mechanical time constant	1.30 ms		
Thermal time constant	30 min		
Shaft torsional stiffness	26000 Nm/rad		
Net weight of the motor	11.4 kg		

Data sheet for SIMOTICS S-1FT7

MLFB-Ordering data

1FT7064-5AF70-1FB1



Figure similar

Optimum operating point		Recommended Motor Module	
Optimum speed	3000 rpm	Rated inverter current	9 A
Optimum power	2.4 kW	Maximum inverter current	27 A
Limiting data		Maximum torque	34.70 Nm
Max. permissible speed (mech.)	9000 rpm		
Max. permissible speed (inverter)	5700 rpm		
Maximum torque	36.0 Nm		
Maximum current	29.0 A		