







Figure similar

Surge suppressor RC element for snapping on 240-400 V AC for contactors size 3...6

product category	Surge suppressor		
product designation	RC element		
General technical data			
certificate of suitability	CE / UL / CSA		
Substance Prohibitance (Date)	07/01/2006		
Weight	0.083 kg		
type of voltage of the control supply voltage	AC		
control supply voltage at AC			
• at 50 Hz rated value	240 ... 400 V		
• at 60 Hz rated value	240 ... 400 V		
control supply voltage frequency			
• 1 rated value	50 Hz		
• 2 rated value	60 Hz		
design of the surge suppressor	RC element		
Ambient conditions			
ambient temperature			
• during operation	-25 ... +55 °C		
• during storage	-40 ... +80 °C		
Approvals Certificates			
General Product Approval	Test Certificates	other	
			
CSA	EG-Konf.	UR	
			Special Test Certificate
			Miscellaneous
other	Environment		
Declaration of Conformity	Confirmation	Environmental Confirmations	

Further information

Information on the packaging
<https://support.industry.siemens.com/cs/ww/en/view/109813875>
 Information- and Downloadcenter (Catalogs, Brochures,...)
<https://www.siemens.com/ic10>
 Industry Mall (Online ordering system)
<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3TX7462-3U>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3TX7462-3U>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3TX7462-3U>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3TX7462-3U&lang=en

last modified:

10/24/2024 