


Technical Information Bulletin - LED

E-Lume™

Date: _____
 In hands date of project: _____
 Project name/Number: _____
 Name of distributor: _____
 Client #: _____
 Name of end user: _____



MOL : 5 7/16 in. (132 mm) Dia. : 4 13/16 in. (122 mm)

ORDERING INFORMATION

Order code: 64903
 Description: LED/P38/ICE/15W/30K/FL/ELUME
 UPC: 69549649033
 Case quantity: 15

PERFORMANCE DATA

Shape: PAR38
 Base: E26
 Wattage (W): 15
 Lamp voltage (VAC): 120
 Colour temperature (K)**: 3 000
 Average life (L70 hours): 25 000
 Initial lumens (lm)*: 1 100
 Initial lumens per watt (lm/W): 73
 CRI: >80
 Beam angle (°): 40
 Power factor: >0.9
 Operating temperature range: -20 °C / -4 °F to 45 °C / 113 °F

*Initial lumens range: +/- 10 %

**Typical colour temperature range: +/- 5 %



DIMMER COMPATIBILITY LIST

Legrand	HCL453P
Cooper	9531AW, AAL06, DAL06P, SLC03P
Leviton	6615, 6674, DSL06-1LZ, IPE04-1LZ, IPL06
Lutron	DVCL-153P, DVCL-253P, DVELV-300P, NTELV-600, SELV-300P

CAUTIONS

- Turn power off before inspection, installation, or removal.
- Suitable for use in open fixtures.
- Suitable for use in wet locations.
- Do not open – no user serviceable parts inside.
- Added weight of the device may cause instability of a freestanding portable luminaire. Use in portable table lamps in which the distance from the bottom of the base to the top of the lampholder does not exceed three (3) times the minimum base diameter.
- Use only on 120 VAC, 60 Hz circuits.
- This device is not intended for use with emergency exit fixtures or emergency exit lights.
- Compatible with most dimmers.
- Three year limited warranty.
- For complete dimmer compatibility and warranty information visit www.standardpro.com.
- Operating temperature: -20 °C/-4 °F to 45 °C/113 °F.

Qty	Description	Price

I accept the specifications of the lamp configuration mentioned above.

Name: _____
 Company: _____
 Signature: _____

Date: _____

Data is based upon tests performed in a controlled environment and representative of relative performance. Actual performance can vary depending on operating conditions. Specifications are subject to change without notice.

June 6, 2016