

Data sheet for SIMOTICS S-1FK7

No image available for this configuration.

MLFB-Ordering data

1FK7043-7AH71-1FB2

Figure similar

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Engineering data

Rated speed (100 K)	4500 rpm
Number of poles	6
Rated torque (100 K)	2.6 Nm
Rated current	4.0 A
Static torque (60 K)	2.50 Nm
Static torque (100 K)	3.1 Nm
Stall current (60 K)	3.60 A
Stall current (100 K)	4.50 A
Moment of inertia	1.140 kgcm ²
Efficiency	90.0 %

Physical constants

Torque constant	0.67 Nm/A
Voltage constant at 20° C	44.0 V/1000*min ⁻¹
Winding resistance at 20° C	1.20 Ω
Rotating field inductance	15.0 mH
Electrical time constant	12.50 ms
Mechanical time constant	0.81 ms
Thermal time constant	40 min
Shaft torsional stiffness	11000 Nm/rad
Net weight of the motor	7.0 kg

Mechanical data

Motor type	Permanent-magnet synchronous motor
Motor type	High Dynamic
Shaft height	48
Cooling	Natural cooling
Radial runout tolerance	0.040 mm
Concentricity tolerance	0.08 mm
Axial runout tolerance	0.08 mm
Vibration severity grade	Grade A
Connector size	1
Degree of protection	IP65 and DE flange IP67
Design acc. to Code I	IM B5 (IM V1, IM V3)
Temperature monitoring	KTY84 temperature sensor in the stator winding
Electrical connectors	Connectors for signals and power rotatable
Color of the housing	without
Holding brake	with holding brake
Shaft extension	Feather key
Encoder system	Encoder AM22DQ: absolute encoder 22 bits (resolution 4194304, encoder-internal 2048 S/R) + 12 bits multi-turn (traversing range 4096 revolutions)

MLFB-Ordering data

1FK7043-7AH71-1FB2

Figure similar

Optimum operating point

Optimum speed	4500 rpm
Optimum power	1.2 kW

Limiting data

Max. permissible speed (mech.)	8000 rpm
Max. permissible speed (inverter)	13100 rpm
Maximum torque	9.4 Nm
Maximum current	14.8 A

Holding brake

Holding brake version	Permanent-magnet brake
Holding torque	4.0 Nm
Power supply voltage	DC 24 V \pm 10 %
Coil current	0.5 A
Opening time	70 ms
Closing time	30 ms
Highest braking work	150 J

Recommended Motor Module

Rated inverter current	5 A
Maximum inverter current	10 A
Maximum torque	6.80 Nm