

Data sheet for SIMOTICS S-1FK7

MLFB-Ordering data

1FK7086-4CC74-1SG2



Figure similar

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Engineering data		Mechanical data			
Rated speed (100 K)	2000 rpm	Motor type	Permanent-magnet synchronous motor		
Number of poles	8	Motor type	High Dynamic		
Rated torque (100 K)	18.0 Nm	Shaft height	80		
Rated current	9.0 A	Cooling	Natural cooling		
Static torque (60 K)	23.00 Nm	Radial runout tolerance	0.050 mm		
Static torque (100 K)	28.0 Nm	Concentricity tolerance	0.10 mm		
Stall current (60 K)	10.70 A	Axial runout tolerance	0.10 mm		
Stall current (100 K)	13.20 A	Vibration severity grade	Grade A		
Moment of inertia	22.000 kgcm ²	Connector size	1		
Efficiency	93.0 %	Degree of protection	IP65 and DE flange IP67		
Physical constants		Design acc. to Code I	IM B5 (IM V1, IM V3)		
		Temperature monitoring	Pt1000 temperature sensor		
		Electrical connectors	Connectors for signals and power rotatable		
		Color of the housing	Standard (Anthracite RAL 7016)		
		Holding brake	without holding brake		
		Shaft extension	Plain shaft		
		Encoder system	Multi-pole resolver (number of pole pairs corresponds to number of pole pairs of the motor)		
		Torque constant	2.12 Nm/A		
		Voltage constant at 20° C	138.0 V/1000*min ⁻¹		
		Winding resistance at 20° C	0.31 Ω		
Rotating field inductance	8.2 mH				
Electrical time constant	26.50 ms				
Mechanical time constant	0.45 ms				
Thermal time constant	65 min				
Shaft torsional stiffness	84000 Nm/rad				
Net weight of the motor	23.0 kg				



Figure similar

MLFB-Ordering data

1FK7086-4CC74-1SG2

Optimum operating point		Recommended Motor Module	
Optimum speed	2000 rpm	Rated inverter current	18 A
Optimum power	3.8 kW	Maximum inverter current	54 A
Limiting data		Maximum torque	90.00 Nm
Max. permissible speed (mech.)	6000 rpm		
Max. permissible speed (inverter)	4200 rpm		
Maximum torque	105.0 Nm		
Maximum current	71.0 A		