



Figure similar

## Data sheet for SIMOTICS M-1PH8

Article No. : 1PH8137-2FM03-1CA1

Client order no. :  
Order no. :  
Offer no. :  
Remarks :

Item no. :  
Consignment no. :  
Project :

### Engineering data

		$P_N$ [kW]	$M_N$ [Nm]	$I_N$ [A]	$U_N$ [V]	$f_N$ [Hz]	$n_N$ [rpm]	$M_{max}$ [Nm]	$I_{max}$ [A]	$n_{max}$ [rpm]	$M_0$ [Nm]	$I_0$ [A]	$\eta$	$\cos \varphi$	$I\mu$ [A]
Y	ALM 400V	62.2	180.0	102.0	405	110.0	3,300	460	303.0	4,500	203.0	115	0.952	0.000	0.0
	BLM/SLM 400V	57.5	183.0	104.0	370	100.0	3,000	460	303.0	4,500	203.0	115	0.953	0.000	0.0
	ALM 480V	69.5	171.0	97.0	479	130.0	3,900	460	303.0	4,500	203.0	115	0.950	0.000	0.0
	BLM/SLM 480V	66.7	177.0	100.0	440	120.0	3,600	460	303.0	4,500	203.0	115	0.950	0.000	0.0

### Mechanical data

Motor type	Permanent-magnet synchronous motor
Shaft height	132
Cooling	Forced ventilation DE -> NDE
Vibration severity grade	S/A
Shaft and flange accuracy	R
Degree of protection	IP55
Design acc. to Code I	IM B35 (IM V15, IM V35)
Temperature monitoring	Pt1000 temperature sensor in the stator winding
Color	Standard (Anthracite RAL 7016)
Type of the bearing	Standard with fixed bearing
Shaft end	Feather key with full key balancing
Encoder system	Absolut encoder 22 bit Singleturn + 12 bit Multiturn, max. encoder speed = 12000 rpm

### External fan

#### Max. power consumption

3 AC 400 V / 50 Hz ( $\pm 10\%$ )	0.10 A
3 AC 400 V / 60 Hz ( $\pm 10\%$ )	0.12 A
3 AC 480 V / 60 Hz ( $\pm 10\%$ )	0.12 A

<sup>1)</sup> at a rated frequency of 4 kHz and a speed range of up to 5000 rpm

### Physical constants

Thermal time constant	10 min
Moment of inertia	885 kgcm <sup>2</sup>
Weight (approx.)	136 kg

### Connection

Type of electrical connection	Terminal box
Position of the connection	NDE top
Power connection	right
Signal connection	DE
Terminal box designation	gk833

### Cooling data and sound pressure level

Airflow, min.	0.09 m <sup>3</sup> /s
Sound pressure level LpA(1m) motor + external fan operation 50 HZ rated load, tolerance + 3dB	70 dB <sup>1)</sup>
Air discharge	axial
Pressure drop	140 Pa