

Data sheet for SIMOTICS S-1FT7



Figure similar

MLFB-Ordering data

1FT7064-5AK70-1BA1

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data		Mechanical data	
Rated speed	6000 rpm	Motor type	Permanent-magnet synchronous motor
Number of poles	10	Design of the motor type	Compact
Rated torque (100 K)	2.9 Nm	Shaft height	63 mm
Rated current	3.4 A	Cooling	Natural cooling
Static torque (60 K)	7.70 Nm	Radial runout tolerance	N
Static torque (100 K)	9.0 Nm	Vibration severity grade	Grade A
Stall current (60 K)	7.7 A	Degree of protection	IP65
Stall current (100 K)	9.0 A	Design acc. to Code I	IM B5 (new flange design)
Rotor moment of inertia	0.0011900 kgm ²	Temperature monitoring	Pt1000 temperature sensor
Efficiency	91.0 %	Color of the housing	
Physical constants		Holding brake version	no value
Torque constant	1.00 Nm/A	Shaft end type	Fitted key and keyway
Voltage constant at 20° C	64.0 V/1000*min ⁻¹	Sensor design	Encoder AS24DQI: Absolut encoder Singleturn 24 bit - with signal connection RJ45
Winding resistance at 20° C	0.39 Ω	Electrical connectors	Connector turnable
Rotating field inductance	4.1 mH	Connector size	1
Electrical time constant	11.00 ms		
Mechanical time constant	1.40 ms		
Thermal time constant	30 min		
Shaft torsional stiffness	26000 Nm/rad		
Net weight of the motor	9.7 kg		

Data sheet for SIMOTICS S-1FT7

MLFB-Ordering data

1FT7064-5AK70-1BA1



Figure similar

Optimum operating point		Recommended Motor Module	
Optimum speed	4500 rpm	Rated inverter current	9 A
Optimum power	2.6 kW	Maximum inverter current	27 A
Limiting data		Maximum torque	25.30 Nm
Max. permissible speed (mech.)	9000 rpm		
Max. permissible speed (inverter)	8000 rpm		
Maximum torque	36.0 Nm		
Maximum current	45.0 A		