

Spare part SIMATIC S7-300 CPU317F-2 PN/DP, Central processing unit with 1024 KB work memory, 1st interface MPI/DP 12 Mbit/s, 2nd interface Ethernet PROFINET, Micro Memory Card required Can be used with software package S7 Distributed Safety from V5.4



Figure similar

General information	
HW functional status	01
Firmware version	V2.6
Engineering with	
<ul style="list-style-type: none"> Programming package 	STEP 7 V5.4 SP2 or higher, S7 Distributed Safety V5.4 or higher
Supply voltage	
Rated value (DC)	
<ul style="list-style-type: none"> 24 V DC 	Yes
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
external protection for power supply lines (recommendation)	2 A min.
Input current	
Current consumption (rated value)	650 mA
Current consumption (in no-load operation), typ.	100 mA
Inrush current, typ.	2.5 A
I^2t	1 A ² ·s

Power loss	
Power loss, typ.	3.5 W
Memory	
Work memory	
• integrated	1 Mbyte; For program and data
• expandable	No
Load memory	
• Plug-in (MMC)	Yes
• Plug-in (MMC), max.	8 Mbyte
• Data management on MMC (after last programming), min.	10 y
Backup	
• present	Yes; Guaranteed by MMC (maintenance-free)
• without battery	Yes; Program and data
CPU processing times	
for bit operations, typ.	0.05 μ s
for bit operations, max.	0.05 μ s
for word operations, typ.	0.2 μ s
for fixed point arithmetic, typ.	0.2 μ s
for floating point arithmetic, typ.	1 μ s
CPU-blocks	
Number of blocks (total)	2 048; (DBs, FCs, FBs); the maximum number of loadable blocks can be reduced by the MMC used.
DB	
• Number, max.	2 047; Number band: 1 to 2047
• Size, max.	64 kbyte
FB	
• Number, max.	2 048; Number range: 0 to 2047
• Size, max.	64 kbyte
FC	
• Number, max.	2 048; Number range: 0 to 2047
• Size, max.	64 kbyte
OB	
• Size, max.	64 kbyte
• Number of free cycle OBs	1; OB 1
• Number of time alarm OBs	1; OB 10
• Number of delay alarm OBs	2; OB 20, 21
• Number of cyclic interrupt OBs	4; OB 32, 33, 34, 35
• Number of process alarm OBs	1; OB 40
• Number of DPV1 alarm OBs	3; OB 55, 56, 57
• Number of isochronous mode OBs	1; OB 61

• Number of startup OBs	1; OB 100
• Number of asynchronous error OBs	6; OB 80, 82, 83, 85, 86, 87
• Number of synchronous error OBs	2; OB 121, 122
Nesting depth	
• per priority class	16
• additional within an error OB	4
Counters, timers and their retentivity	
S7 counter	
• Number	512
Retentivity	
— adjustable	Yes
— lower limit	0
— upper limit	511
— preset	8
Counting range	
— adjustable	Yes
— lower limit	0
— upper limit	999
IEC counter	
• present	Yes
• Type	SFB
• Number	Unlimited (limited only by RAM capacity)
S7 times	
• Number	512
Retentivity	
— adjustable	Yes
— lower limit	0
— upper limit	511
— preset	No retentivity
Time range	
— lower limit	10 ms
— upper limit	9 990 s
IEC timer	
• present	Yes
• Type	SFB
• Number	Unlimited (limited only by RAM capacity)
Data areas and their retentivity	
retentive data area in total	All, max. 256 KB
Flag	
• Number, max.	4 096 byte
• Retentivity available	Yes; From MB 0 to MB 4 095

• Retentivity preset	MB 0 to MB 15
• Number of clock memories	8; 1 memory byte
Data blocks	
• Retentivity adjustable	Yes; via non-retain property on DB
• Retentivity preset	Yes
Local data	
• per priority class, max.	1 024 byte
Address area	
I/O address area	
• Inputs	8 kbyte
• Outputs	8 kbyte
of which distributed	
— Inputs	8 kbyte
— Outputs	8 kbyte
Process image	
• Inputs	2 048 byte
• Outputs	2 048 byte
• Inputs, adjustable	2 048 byte
• Outputs, adjustable	2 048 byte
• Inputs, default	1 024 byte
• Outputs, default	1 024 byte
Digital channels	
• Inputs	65 536
— of which central	1 024
• Outputs	65 536
— of which central	1 024
Analog channels	
• Inputs	4 096
— of which central	256
• Outputs	4 096
— of which central	256
Hardware configuration	
Number of expansion units, max.	3
Number of DP masters	
• integrated	1
• via CP	4
Number of operable FMs and CPs (recommended)	
• FM	8
• CP, PtP	8
• CP, LAN	10
Rack	

- Racks, max. 4
- Modules per rack, max. 8

Time of day

Clock

- Hardware clock (real-time) Yes
- retentive and synchronizable Yes
- Backup time 6 wk; At 40 °C ambient temperature
- Deviation per day, max. 10 s

Operating hours counter

- Number 4
- Number/Number range 0 to 3
- Range of values 0 to 2³¹ hours (when using SFC 101)
- Granularity 1 h
- retentive Yes; Must be restarted at each restart

Clock synchronization

- supported Yes
- to MPI, master Yes
- to MPI, slave Yes
- to DP, master Yes; With DP slave only slave clock
- to DP, slave Yes
- in AS, master Yes
- in AS, slave Yes

Digital inputs

integrated channels (DI) 0

Digital outputs

integrated channels (DO) 0

Analog inputs

integrated channels (AI) 0

Analog outputs

integrated channels (AO) 0

Interfaces

Number of industrial Ethernet interfaces 1

Number of PROFINET interfaces 1

Number of RS 485 interfaces 2

Number of RS 422 interfaces 0

1. Interface

Interface type Integrated RS 485 interface

Physics RS 485

Isolated Yes

Power supply to interface (15 to 30 V DC), max.	200 mA
Protocols	
• MPI	Yes
• PROFIBUS DP master	Yes
• PROFIBUS DP slave	Yes
• Point-to-point connection	No
MPI	
• Number of connections	16
• Transmission rate, max.	12 Mbit/s
Services	
— PG/OP communication	Yes
— Routing	Yes
— Global data communication	Yes
— S7 basic communication	Yes
— S7 communication	Yes
— S7 communication, as client	No
— S7 communication, as server	Yes
PROFIBUS DP master	
• Transmission rate, max.	12 Mbit/s
• Number of DP slaves, max.	124
Services	
— PG/OP communication	Yes
— Routing	Yes
— Global data communication	No
— S7 basic communication	Yes
— S7 communication	Yes
— S7 communication, as client	No
— S7 communication, as server	Yes
— Equidistance	Yes
— Isochronous mode	Yes; OB 61
— SYNC/FREEZE	Yes
— Activation/deactivation of DP slaves	Yes
— DPV1	Yes
PROFIBUS DP slave	
• Transmission rate, max.	12 Mbit/s
• automatic baud rate search	Yes; only with passive interface
• Address area, max.	32
• User data per address area, max.	32 byte
Services	
— Routing	Yes; with interface active
— Global data communication	No

— S7 basic communication	Yes
— S7 communication	Yes
— S7 communication, as client	No
— S7 communication, as server	Yes
— Direct data exchange (slave-to-slave communication)	Yes
— DPV1	No
Transfer memory	
— Inputs	244 byte
— Outputs	244 byte

2. Interface

Interface type	PROFINET
Physics	Ethernet
Isolated	Yes
Power supply to interface (15 to 30 V DC), max.	0 mA
automatic detection of transmission rate	Yes; 10/100 Mbit/s
Protocols	
• MPI	No
• PROFINET IO Controller	Yes; Firmware version V2.3 and higher
• PROFINET CBA	Yes
• PROFIBUS DP master	No
• PROFIBUS DP slave	No
• Point-to-point connection	No
PROFINET IO Controller	
• Transmission rate, max.	100 Mbit/s
Services	
— PG/OP communication	Yes
— Routing	Yes
— S7 communication	Yes; with loadable FBs, max. configurable connections: 16, max. number of instances: 32
— Open IE communication	Yes; via TCP/IP
— Number of connectable IO Devices, max.	128
— Updating time	1 to 512 ms (minimum value depends on communication share set for PROFINET I/O, on the number of I/O devices, and on the volume of configured user data)
Address area	
— Inputs, max.	8 kbyte
— Outputs, max.	8 kbyte
— User data consistency, max.	256 byte
PROFINET CBA	
• acyclic transmission	Yes
• cyclic transmission	Yes

Protocols

Open IE communication

- | | |
|-------------------------------|---|
| • TCP/IP | Yes; via integrated PROFINET interface and loadable FBs |
| — Number of connections, max. | 8 |
| — Data length, max. | 1 460 byte |

Communication functions

PG/OP communication Yes

Global data communication

- | | |
|---|---------|
| • supported | Yes |
| • Number of GD loops, max. | 8 |
| • Number of GD packets, max. | 8 |
| • Number of GD packets, transmitter, max. | 8 |
| • Number of GD packets, receiver, max. | 8 |
| • Size of GD packets, max. | 22 byte |
| • Size of GD packet (of which consistent), max. | 22 byte |

S7 basic communication

- | | |
|---|--|
| • supported | Yes |
| • User data per job, max. | 76 byte |
| • User data per job (of which consistent), max. | 76 byte; 76 bytes (with X_SEND or X_RCV); 64 bytes (with X_PUT or X_GET as server) |

S7 communication

- | | |
|---------------------------|---|
| • supported | Yes |
| • as server | Yes |
| • as client | Yes; via integrated PROFINET interface and loadable FB or via CP and loadable FB |
| • User data per job, max. | See online help of STEP 7 (shared parameters of the SFBs/FBs and of the SFCs/FCs of S7 Communication) |

S5 compatible communication

- | | |
|-------------|-----------------------------|
| • supported | Yes; via CP and loadable FC |
|-------------|-----------------------------|

PROFINET CBA (at set setpoint communication load)

- | | |
|--|------------|
| • Setpoint for the CPU communication load | 50 % |
| • Number of remote interconnection partners | 32 |
| • Number of functions, master/slave | 17 |
| • Total of all master/slave connections | 1 000 |
| • Data length of all incoming connections master/slave, max. | 4 000 byte |
| • Data length of all outgoing connections master/slave, max. | 4 000 byte |
| • Number of device-internal and PROFIBUS interconnections | 500 |
| • Data length of device-internal und PROFIBUS interconnections, max. | 4 000 byte |

• Data length per connection, max.	1 400 byte
Remote interconnections with acyclic transmission	
— Sampling frequency: Sampling time, min.	500 ms
— Number of incoming interconnections	100
— Number of outgoing interconnections	100
— Data length of all incoming interconnections, max.	2 000 byte
— Data length of all outgoing interconnections, max.	2 000 byte
— Data length per connection, max.	1 400 byte
Remote interconnections with cyclic transmission	
— Transmission frequency: Transmission interval, min.	10 ms
— Number of incoming interconnections	200
— Number of outgoing interconnections	200
— Data length of all incoming interconnections, max.	2 000 byte
— Data length of all outgoing interconnections, max.	2 000 byte
— Data length per connection, max.	450 byte
HMI variables via PROFINET (acyclic)	
— Number of stations that can log on for HMI variables (PN OPC/iMap)	3; 2x PN OPC/1x iMap
— HMI variable updating	500 ms
— Number of HMI variables	200
— Data length of all HMI variables, max.	2 000 byte
PROFIBUS proxy functionality	
— supported	Yes
— Number of linked PROFIBUS devices	16
— Data length per connection, max.	240 byte; Slave-dependent
Number of connections	
• overall	32
• usable for PG communication	31
— reserved for PG communication	1
— adjustable for PG communication, min.	1
— adjustable for PG communication, max.	31
• usable for OP communication	31
— reserved for OP communication	1
— adjustable for OP communication, min.	1
— adjustable for OP communication, max.	31
• usable for S7 basic communication	30
— reserved for S7 basic communication	0

- adjustable for S7 basic communication, min. 0
- adjustable for S7 basic communication, max. 30

S7 message functions

Number of login stations for message functions, max.	32; Depending on the configured connections for PG/OP and S7 basic communication
Process diagnostic messages	Yes
simultaneously active Alarm-S blocks, max.	60

Test commissioning functions

Status block	Yes
Single step	Yes
Number of breakpoints	2

Status/control

- Status/control variable Yes
- Variables Inputs, outputs, memory bits, DB, times, counters
- Number of variables, max. 30
 - of which status variables, max. 30
 - of which control variables, max. 14

Forcing

- Forcing Yes
- Forcing, variables Inputs, outputs
- Number of variables, max. 10

Diagnostic buffer

- present Yes
- Number of entries, max. 100
 - adjustable No

Configuration

Configuration software	
• STEP 7	Yes; V5.3 SP3 and higher + HW update

Programming

- Command set see instruction list
- Nesting levels 8
- System functions (SFC) see instruction list
- System function blocks (SFB) see instruction list

Programming language

- LAD Yes
- FBD Yes
- STL Yes
- SCL Yes
- CFC Yes

— GRAPH

Yes

— HiGraph®

Yes

Know-how protection

- User program protection/password protection

Yes

Dimensions

Width

80 mm

Height

125 mm

Depth

130 mm

Weights

Weight, approx.

460 g

last modified:

08/27/2019