

30mm Command/52, Chrome Finish Heavy Duty, Watertight/Oiltight Complete Metal Unit Illuminated Push-Pull Operator Full Voltage, 12V AC/DC Incandescent Lamp Mushroom Head Cap Small 1 3/4" (44.5 mm) Plastic, Amber 3 Position Pull-Momentary/Push-Maintained UL Listed, CSA Certified NEMA 1,3,3R,4,4X,12,13 & Automotive Standards

Design of the product	Actuator round
Enclosure	
Number of command points	1
Delivery state	No
<ul style="list-style-type: none"> • as a kit 	
Actuator	
Product extension optional Light source	Yes
Color	
<ul style="list-style-type: none"> • of the actuating element 	amber
Material of the actuating element	plastic
Type of unlocking device	pull-to-unlatch mechanism
Number of switching positions	3
Front ring	
Product component front ring	Yes
Design of the front ring	standard
Material of the front ring	metal
Color of the front ring	chrome
Holder	
Material of the holder	Metal
Contact block/ lampholder	
Mounting type	BA 9s with lamp
Number of lampholders	1
Display	
Number of LED modules	0
General technical data	
Product component	
<ul style="list-style-type: none"> • lamp transformer 	No
<ul style="list-style-type: none"> • Light source 	Yes
Degree of pollution	1
Type of voltage	

<ul style="list-style-type: none"> • of the operating voltage 	AC/DC
<ul style="list-style-type: none"> • of the input voltage 	AC/DC
Surge voltage resistance rated value	4 kV
Protection class IP	IP66
<ul style="list-style-type: none"> • of the terminal 	IP20
Operating voltage	
<ul style="list-style-type: none"> • at AC <ul style="list-style-type: none"> — at 60 Hz rated value 	12 ... 13 V
<ul style="list-style-type: none"> • at DC rated value 	12 ... 13 V

Supply voltage

Type of voltage of the supply voltage	
<ul style="list-style-type: none"> • of the light source 	AC/DC
Supply voltage of the light source at AC	
<ul style="list-style-type: none"> • at 60 Hz rated value 	12 V
Supply voltage of the light source at DC	
<ul style="list-style-type: none"> • rated value 	12 V

Connections/ Terminals

Type of electrical connection	screw-type terminals
<ul style="list-style-type: none"> • of modules and accessories 	Screw-type terminal
Tightening torque of the screws in the bracket	20 N·m
Tightening torque [lbf·in]	
<ul style="list-style-type: none"> • with screw-type terminals 	8 ... 8 lbf·in

Lamp

Type of light source	filament lamp
Color of the light source	clear

Safety related data

Protection against electrical shock	finger-safe
--	-------------

Ambient conditions

Ambient temperature	
<ul style="list-style-type: none"> • during operation 	-35 ... +70 °C
<ul style="list-style-type: none"> • during storage 	-40 ... +85 °C

Installation/ mounting/ dimensions

Shape of the installation opening	round
--	-------

Certificates/ approvals

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=US2:52PP7CT>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=US2:52PP7CT>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/US2:52PP7CT>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=US2:52PP7CT&lang=en

last modified:

02/14/2020