

Data sheet for SIMOTICS S-1FK7



Figure similar

MLFB-Ordering data

1FK7044-4CF71-1TB0

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

| Engineering data | | Mechanical data | |
|-----------------------------|-------------------------------|--------------------------|--|
| Rated speed (100 K) | 3000 rpm | Motor type | Permanent-magnet synchronous motor |
| Number of poles | 6 | Motor type | High Dynamic |
| Rated torque (100 K) | 3.7 Nm | Shaft height | 48 |
| Rated current | 3.5 A | Cooling | Natural cooling |
| Static torque (60 K) | 3.75 Nm | Radial runout tolerance | 0.040 mm |
| Static torque (100 K) | 4.5 Nm | Concentricity tolerance | 0.08 mm |
| Stall current (60 K) | 3.20 A | Axial runout tolerance | 0.08 mm |
| Stall current (100 K) | 4.00 A | Vibration severity grade | Grade A |
| Moment of inertia | 1.620 kgcm ² | Connector size | 1 |
| Efficiency | 91.0 % | Degree of protection | IP64 |
| Physical constants | | Design acc. to Code I | IM B5 (IM V1, IM V3) |
| Torque constant | 1.13 Nm/A | Temperature monitoring | KTY84 temperature sensor in the stator winding |
| Voltage constant at 20° C | 72.0 V/1000*min ⁻¹ | Electrical connectors | Connectors for signals and power rotatable |
| Winding resistance at 20° C | 1.49 Ω | Color of the housing | Standard (Anthracite RAL 7016) |
| Rotating field inductance | 18.8 mH | Holding brake | with holding brake |
| Electrical time constant | 12.60 ms | Shaft extension | Feather key |
| Mechanical time constant | 0.44 ms | Encoder system | Resolver 2-pole |
| Thermal time constant | 45 min | | |
| Shaft torsional stiffness | 7900 Nm/rad | | |
| Net weight of the motor | 8.0 kg | | |



Figure similar

MLFB-Ordering data

1FK7044-4CF71-1TB0

Optimum operating point

| | |
|---------------|----------|
| Optimum speed | 3000 rpm |
| Optimum power | 1.2 kW |

Limiting data

| | |
|-----------------------------------|----------|
| Max. permissible speed (mech.) | 9000 rpm |
| Max. permissible speed (inverter) | 8050 rpm |
| Maximum torque | 13.0 Nm |
| Maximum current | 12.1 A |

Holding brake

| | |
|-----------------------|------------------------|
| Holding brake version | Permanent-magnet brake |
| Holding torque | 4.0 Nm |
| Power supply voltage | DC 24 V \pm 10 % |
| Coil current | 0.5 A |
| Opening time | 70 ms |
| Closing time | 30 ms |
| Highest braking work | 150 J |

Recommended Motor Module

| | |
|--------------------------|----------|
| Rated inverter current | 5 A |
| Maximum inverter current | 15 A |
| Maximum torque | 13.00 Nm |