

## Data sheet for SIMOTICS S-1FK7

MLFB-Ordering data

1FK7101-2AC71-1UH0



Figure similar

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Engineering data	
Rated speed (100 K)	2000 rpm
Number of poles	8
Rated torque (100 K)	20.5 Nm
Rated current	9.7 A
Static torque (60 K)	22.50 Nm
Static torque (100 K)	27.0 Nm
Stall current (60 K)	10.00 A
Stall current (100 K)	12.30 A
Moment of inertia	87.000 kgcm <sup>2</sup>
Efficiency	93.0 %

Physical constants	
Torque constant	2.15 Nm/A
Voltage constant at 20° C	144.5 V/1000*min <sup>-1</sup>
Winding resistance at 20° C	0.34 Ω
Rotating field inductance	8.5 mH
Electrical time constant	25.00 ms
Mechanical time constant	1.62 ms
Thermal time constant	60 min
Shaft torsional stiffness	116000 Nm/rad
Net weight of the motor	27.5 kg

Mechanical data	
Motor type	Permanent-magnet synchronous motor
Motor type	Compact
Shaft height	100
Cooling	Natural cooling
Radial runout tolerance	0.050 mm
Concentricity tolerance	0.10 mm
Axial runout tolerance	0.10 mm
Vibration severity grade	Grade A
Connector size	1.5
Degree of protection	IP64
Design acc. to Code I	IM B5 (IM V1, IM V3)
Temperature monitoring	Pt1000 temperature sensor
Electrical connectors	Connectors for signals and power rotatable
Color of the housing	Standard (Anthracite RAL 7016)
Holding brake	with holding brake
Shaft extension	Plain shaft
Encoder system	Resolver R15DQ: resolver 15 bits (resolution 32768, internal multi-pole)



Figure similar

## MLFB-Ordering data

1FK7101-2AC71-1UH0

### Optimum operating point

Optimum speed	2000 rpm
Optimum power	4.3 kW

### Limiting data

Max. permissible speed (mech.)	5000 rpm
Max. permissible speed (inverter)	4000 rpm
Maximum torque	80.0 Nm
Maximum current	40.5 A

### Holding brake

Holding brake version	Permanent-magnet brake
Holding torque	43.0 Nm
Power supply voltage	DC 24 V $\pm$ 10 %
Coil current	1.0 A
Opening time	300 ms
Closing time	70 ms
Highest braking work	3380 J

### Recommended Motor Module

Rated inverter current	18 A
Maximum inverter current	54 A
Maximum torque	80.00 Nm