



Figure similar

Data sheet for SIMOTICS M-1PH8

Article No. : **1PH8165-2EL02-0GB2-Z**
X01

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data

		P _N [kW]	M _N [Nm]	I _N [A]	U _N [V]	f _N [Hz]	n _N [rpm]	M _{max} [Nm]	I _{max} [A]	n _{max} [rpm]	M ₀ [Nm]	I ₀ [A]	η	cos φ	I _μ [A]
Y	ALM 400V	87.0	300.0	138.0	410	187.0	2,800	1,135	551.0	4,000	440.0	188	0.959	0.000	0.0
	BLM/SLM 400V	84.0	320.0	148.0	370	167.0	2,500	1,135	551.0	4,000	440.0	188	0.955	0.000	0.0
	ALM/BLM/SLM 480V	89.0	285.0	131.0	440	200.0	3,000	1,135	551.0	4,000	440.0	188	0.960	0.000	0.0

Mechanical data

Motor type	Permanent-magnet synchronous motor
Shaft height	160
Cooling	Forced ventilation DE -> NDE
Vibration severity grade	R/A
Shaft and flange accuracy	R
Degree of protection	IP55
Design acc. to Code I	IM B5 (IM V1, IM V3)
Temperature monitoring	Pt1000 temperature sensor in the stator winding
Color	Jet black, matt RAL 9005
Type of the bearing	Standard
Shaft end	Plain shaft
Encoder system	Absolut encoder EnDat 2048 S/R, max. encoder speed = 12000 rpm

Physical constants

Thermal time constant	10 min
Moment of inertia	2,160 kgcm ²
Weight (approx.)	218 kg

Connection

Type of electrical connection	Terminal box
Position of the connection	NDE top
Power connection	left
Signal connection	DE
Terminal box designation	gk874

Cooling data and sound pressure level

Airflow, min.	0.16 m ³ /s
Sound pressure level LpA(1m) motor + external fan operation 50 HZ rated load, tolerance + 3dB	73 dB ¹⁾
Air discharge	axial
Pressure drop	200 Pa

External fan

Max. power consumption

3 AC 400 V / 50 Hz (±10%)	0.16 A
3 AC 400 V / 60 Hz (±10%)	0.21 A
3 AC 480 V / 60 Hz (±10%)	0.21 A

Special design

X01 Paint finish: Jet black, matt RAL 9005

¹⁾ at a rated frequency of 4 kHz and a speed range of up to 5000 rpm