



OUTPUT COUPLER WITH PLUGGABLE RELAY, 1 CHANGEOVER CONTACT SPRING-LOADED TERMINAL 115 V AC/DC CASING WIDTH 6.2 MM

Figure similar

General technical data:	
Type of voltage	AC/DC
Supply voltage frequency for auxiliary and control current circuit Rated value	50 ... 60 Hz
Control supply voltage	
<ul style="list-style-type: none"> • with AC <ul style="list-style-type: none"> — at 50 Hz Rated value <ul style="list-style-type: none"> — minimum 115 V — maximum 115 V — at 60 Hz Rated value <ul style="list-style-type: none"> — minimum 115 V — maximum 115 V • for DC Rated value <ul style="list-style-type: none"> — minimum 115 V — maximum 115 V 	
Switching behavior	monostable
Number of NC contacts for auxiliary contacts	0
Number of NO contacts for auxiliary contacts	0
Number of CO contacts for auxiliary contacts	1
Operating current of the auxiliary contacts	
<ul style="list-style-type: none"> • at DC-13 <ul style="list-style-type: none"> — at 24 V 1 A — at 110 V 0.2 A — at 230 V 0.1 A • at AC-15 	

— at 230 V

3 A

Equipment marking acc. to DIN 40719 extended according to IEC 204-2 acc. to IEC 750

K

Equipment marking acc. to DIN EN 61346-2

K



Mechanical data:

Type of electrical connection	spring-loaded terminals
Type of electrical connection Plug-in socket	Yes
Design of the relay operating mechanism	poled
Design of the switching function positively driven	No
Product component Plug-in socket	Yes
Width	6.2 mm
Height	89.5 mm
Depth	92 mm

Ambient conditions:

Protection class IP	IP20
Ambient temperature during operation	-25 ... +55 °C

Certificates/ approvals:

General Product Approval	Test Certificates	other
 CCC	 UL	Special Test Certificate Declaration of Conformity Confirmation

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)
<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)
<http://www.siemens.com/industrymall>

Cax online generator
<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3TX70151BE00>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
<https://support.industry.siemens.com/cs/ww/en/ps/3TX70151BE00>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)
http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3TX70151BE00&lang=en

last modified:

05.05.2015