

SIMATIC IPC BX-59A (box PC); mainboard (chipset R680E); 4x Gigabit Ethernet (IE/PN) RJ45; 6x USB 3.1 generation 2; 1x USB-C, 2x serial (COM); 2x DP; audio; 2x SIM slots; 2xM.2 flex module slots internal; RAID controller onboard; watchdog,temperature/fan monitoring; EM2: PCIe x 16 gen4 + graphics card NVIDIA L4 and PCIe x 4 and 1 dual-port 10 GB fiber card; with 1 SFP+ transceiver Core i5-13500E, 65 W; 14C(6P+8E)/20T; 2.4(4.6) GHz; with 24 V DC, 400 W power supply 512 GB M.2 NVME onboard SSD 16 GB DDR5(1\*16) NVRAM (M.2) no power supply unit cable Windows 10 Enterprise LTSC 2021, 64-bit, MUI for Core i5 (with USB-Stick restore image; D&D) expansion module without memory

General information	
Product type designation	BX-59A
Installation type/mounting	
Mounting	Wall mounting, book mounting, desk mounting, tower mounting
Design	Box PC, built-in unit
Supply voltage	
Type of supply voltage	400 W / 24 V / 19.2 - 28.8 VDC; 220 W / 12-24 V / 9 - 36 VDC
Rated value (DC)	24 V; 12...24 V DC on 220 W
Mains buffering	
<ul style="list-style-type: none"> <li>Mains/voltage failure stored energy time</li> </ul>	20 ms
Processor	
Processor type	Core i9-13900E 24C (8P+16E)/32T, 1.8 (5.2) GHz, 36 MB cache; Core i7-13700E 16C (8P+8E)/24T, 1.9 (5.1) GHz, 30 MB cache; Core i7-13700TE 16C (8P+8E)/24T, 1.1 (4.8) GHz, 30 MB cache; Core i5-13500E 14C (6P+8E)/20T, 2.4 (4.6) GHz, 24 MB cache
Chipset	Intel R680E
Graphic	
Graphics controller	Intel UHD Graphics 770 (Core i5, Core i7, Core i9)
Drives	
SSD	Yes; base module: 480 GB 2.5" SATA SSD (PLP); 960 GB 2.5" SATA SSD (PLP); 512 GB 2.5" SATA SSD; 1 TB 2.5" SATA SSD; 512 GB M.2 NVME onboard SSD; 1 TB M.2 NVME onboard SSD; 512 GB M.2 NVME onboard SSD with 1* 512 GB M.2 NVME on 1 exchangeable SSD slider; 512 GB M.2 NVME onboard SSD with 1* 1 TB M.2 NVME on 1 exchangeable SSD slider; RAID1 2* 512 GB M.2 NVME on 2 exchangeable SSD slider; RAID1 2* 1 TB M.2 NVME on 2 exchangeable SSD slider; 512 GB M.2 NVME onboard SSD with RAID1 2* 512 GB M.2 NVME on 2 exchangeable SSD slider
Memory	
Type of memory	DDR5-4800 SO-DIMM
Main memory	8 / 16 / 32 / 64 GB; ECC optional
Capacity of main memory, max.	64 Gbyte
Data areas and their retentivity	
Retentive data area (incl. timers, counters, flags), max.	512 kbyte; 128 KB can be stored in the buffer time
Hardware configuration	
Slots	
<ul style="list-style-type: none"> <li>free slots</li> </ul>	2 slots: 1x PCI Express (x16) gen 4 (16 lanes) and 1x PCI Express (x4) gen 3 (4 lanes)
Interfaces	
Number of industrial Ethernet interfaces	4; 4x Gigabit Ethernet (RJ45)
USB port	1x USB 3.2 Gen2 10G Type C, 6x USB 3.2 Gen 2 10G Type A
Connection for keyboard/mouse	USB / USB
serial interface version	2x / 4x (optional) COM (RS 232 / 485 / 422; selectable)
Multimedia	
<ul style="list-style-type: none"> <li>Audio In/Out</li> </ul>	Yes
Video interfaces	
<ul style="list-style-type: none"> <li>Graphics interface</li> </ul>	2x DisplayPort
Industrial Ethernet	
<ul style="list-style-type: none"> <li>Industrial Ethernet interface                             <ul style="list-style-type: none"> <li>— 100 Mbps</li> </ul> </li> </ul>	4x Gigabit Ethernet (RJ45) Yes

— 1000 Mbps	Yes
<b>Interrupts/diagnostics/status information</b>	
LED status display	base module (1x power, 3x user, 1x HDD)
<b>Integrated Functions</b>	
<b>Monitoring functions</b>	
• Temperature monitoring	Yes
• Watchdog	Yes
• Fan	Yes
• Monitoring function via network	Optional
<b>EMC</b>	
<b>Interference immunity against discharge of static electricity</b>	
• Interference immunity against discharge of static electricity	±6 kV contact; ±8 kV air (to IEC 1000-4-2; ESD)
<b>Interference immunity against high-frequency electromagnetic fields</b>	
• Interference immunity against high frequency radiation	10 V/m, 80 MHz to 2 700 MHz, 80 % AM acc. to IEC 61000-4-3; 3 V/m, 2.7 GHz to 6 GHz, 80 % AM acc. to IEC 61000-4-3; 10 V, 10 kHz to 80 MHz, 80 % AM acc. to IEC 61000-4-6
<b>Interference immunity to cable-borne interference</b>	
• Interference immunity on supply cables	±2 kV (according to IEC 61000-4-4, burst); ±1 kV (according to IEC 61000-4-5, surge pulse/line to line); ±2 kV (according to IEC 61000-4-5, surge pulse/line to ground)
• Interference immunity on signal cables >30m	burst: ±2 kV (5 kHz / 100 kHz) in accordance with IEC 61000-4-4; length of signal port extension cable ≥ 30 m; surge: ±2 kV line-to-earth in accordance with IEC 61000-4-5; length of signal port extension cable ≥ 10 m
• Interference immunity on signal cables < 30m	burst: ±1 kV (5 kHz / 100 kHz) in accordance with IEC 61000-4-4; length of signal port extension cable < 30 m; surge: ±2 kV line-to-earth in accordance with IEC 61000-4-5; length of signal port extension cable ≥ 10 m
<b>Interference immunity to magnetic fields</b>	
• Interference immunity to magnetic fields at 50 Hz	100 A/m; to IEC 61000-4-8
<b>Emission of conducted and non-conducted interference</b>	
• Interference emission via line/AC current cables	EN 61000-6-3, EN 61000-6-4, CISPR 22 Class B, FCC Class A
<b>Compliance with line harmonic distortion limits</b>	
• Compliance with line harmonic distortion acc. to IEC 61000-3-2, IEC 61000-3-3	Yes; EN 61000-3-2 Class D; EN 61000-3-3
<b>Degree and class of protection</b>	
IP degree of protection	IP20 with fan, IP40 without fan
<b>Standards, approvals, certificates</b>	
CE mark	Yes; also UKCA
cULus	Yes
RCM (formerly C-TICK)	Yes
FCC	Yes
EMC	EMC EN 61000-6-1, EN IEC 61000-6-1, EN 61000-6-2, EN IEC 61000-6-3, EN IEC 61000-6-4
<b>Ambient conditions</b>	
<b>Ambient temperature during operation</b>	
• min.	0 °C
• max.	55 °C; base module only: 40 °C at fanless and 2.5" non power loss protection SSD configuration; 50 °C at fanless and M.2 SSD configuration; with extension module: 40 °C
<b>Ambient temperature during storage/transportation</b>	
• min.	-20 °C
• max.	60 °C
<b>Relative humidity</b>	
• Relative humidity	tested according to IEC 60068-2-78, IEC 60068-2-30: operation: 5 % to 85 % at 30 °C (no condensation) storage: 5 % to 95 % at 25 °C / 55 °C (no condensation)
<b>Vibrations</b>	
• Vibration resistance during operation acc. to IEC 60068-2-6	tested in accordance with IEC 60068-2-6; operation - base module (5 to 8.4 Hz: 3.5 mm; 8.4 to 200 Hz: 9.8 m/s <sup>2</sup> ); extension module w/o storages (10 to 58 Hz: 0.0375 mm; 58 to 200 Hz: 4.9 m/s <sup>2</sup> ); extension module with HDD (10 to 58 Hz: 0.015 mm; 58 to 200 Hz: 1.96 m/s <sup>2</sup> ); extension module with SSD (10 to 58 Hz: 0.0375 mm; 58 to 200 Hz: 4.9 m/s <sup>2</sup> ); storage / transport - 5 to 8.4 Hz: 3.5 mm; 8.4 to 500 Hz: 9.8 m/s <sup>2</sup>
<b>Shock testing</b>	
• Shock load during operation	tested in accordance with IEC 60068-2-27; operation - base module (150 m/s <sup>2</sup> , 11 ms); extension module w/o HDD (150 m/s <sup>2</sup> , 11 ms); extension module with HDD (10 m/s <sup>2</sup> , 20 ms); storage / transport - 250 m/s <sup>2</sup> , 6 ms

Operating systems	
pre-installed operating system	Windows 10 Enterprise 2021 LTSC 64-bit, MUI
without operating system	Yes; Optional
pre-installed operating system	
• Windows 10 Enterprise	Yes; Windows 10 Enterprise 2021 LTSC 64-bit, MUI
Software	
SIMATIC Software	optionally with pre-installed Industrial Edge - SIMATIC
Dimensions	
Width	79 mm; 85 mm base module with fan module, 137 mm with extension module 2 slots
Height	194 mm
Depth	237 mm; 307 mm base module with fan module and with / without extension module 2 slots

### Approvals / Certificates

General Product Approval	Environment
--------------------------	-------------



[Miscellaneous](#)



### Environment



last modified:

3/4/2025