

## Data sheet for SIMOTICS S-1FT7



Figure similar

### MLFB-Ordering data

**1FT7044-5AF71-1FH1-Z**  
X09

Client order no. :  
Order no. :  
Offer no. :  
Remarks :

Item no. :  
Consignment no. :  
Project :

Engineering data		Mechanical data	
Rated speed	3000 rpm	Motor type	Permanent-magnet synchronous motor
Number of poles	6	Design of the motor type	Compact
Rated torque (100 K)	4.3 Nm	Shaft height	48 mm
Rated current	2.6 A	Cooling	Natural cooling
Static torque (60 K)	4.40 Nm	Radial runout tolerance	N
Static torque (100 K)	5.0 Nm	Vibration severity grade	Grade A
Stall current (60 K)	2.5 A	Degree of protection	IP65
Stall current (100 K)	2.8 A	Design acc. to Code I	IM B5 (compatible with 1FT6)
Rotor moment of inertia	0.0006300 kgm <sup>2</sup>	Temperature monitoring	Pt1000 temperature sensor
Efficiency	92.0 %	Color of the housing	Anthracite RAL 7016
Physical constants		Holding brake version	Permanent-magnet brake
Torque constant	1.74 Nm/A	Shaft end type	Plain shaft
Voltage constant at 20° C	110.5 V/1000*min <sup>-1</sup>	Sensor design	Encoder AM22DQ: absolute encoder 22 bits (resolution 4194304, encoder-internal 2048 S/R) + 12 bits multi-turn (traversing range 4096 revolutions)
Winding resistance at 20° C	2.35 Ω	Electrical connectors	Connector turnable
Rotating field inductance	15.0 mH	Connector size	1
Electrical time constant	6.40 ms		
Mechanical time constant	1.30 ms		
Thermal time constant	35 min		
Shaft torsional stiffness	9500 Nm/rad		
Net weight of the motor	8.1 kg		

## Data sheet for SIMOTICS S-1FT7

MLFB-Ordering data

1FT7044-5AF71-1FH1-Z  
X09



Figure similar

Optimum operating point		Recommended Motor Module	
Optimum speed	3000 rpm	Rated inverter current	3 A
Optimum power	1.4 kW	Maximum inverter current	9 A
Limiting data		Maximum torque	14.80 Nm
Max. permissible speed (mech.)	9000 rpm	Special design	
Max. permissible speed (inverter)	5200 rpm	X09	Paint finish anthracite, similar to RAL 7016
Maximum torque	23.0 Nm		
Maximum current	16.0 A		