

Data sheet for SIMOTICS S-1FK7



Figure similar

MLFB-Ordering data

1FK7062-2AC74-1AA0

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Engineering data		Mechanical data			
Rated speed (100 K)	2000 rpm	Motor type	Permanent-magnet synchronous motor		
Number of poles	8	Motor type	Compact		
Rated torque (100 K)	7.0 Nm	Shaft height	63		
Rated current	2.6 A	Cooling	Natural cooling		
Static torque (60 K)	7.10 Nm	Radial runout tolerance	0.040 mm		
Static torque (100 K)	8.5 Nm	Concentricity tolerance	0.10 mm		
Stall current (60 K)	2.45 A	Axial runout tolerance	0.10 mm		
Stall current (100 K)	3.00 A	Vibration severity grade	Grade A		
Moment of inertia	11.200 kgcm ²	Connector size	1		
Efficiency	90.0 %	Degree of protection	IP64		
<th colspan="2">Physical constants</th> <td>Design acc. to Code I</td> <td>IM B5 (IM V1, IM V3)</td>		Physical constants		Design acc. to Code I	IM B5 (IM V1, IM V3)
		Torque constant	2.83 Nm/A	Temperature monitoring	Pt1000 temperature sensor
		Voltage constant at 20° C	180.5 V/1000*min ⁻¹	Electrical connectors	Connectors for signals and power rotatable
		Winding resistance at 20° C	3.59 Ω	Color of the housing	Standard (Anthracite RAL 7016)
		Rotating field inductance	45.5 mH	Holding brake	without holding brake
		Electrical time constant	12.70 ms	Shaft extension	Feather key
		Mechanical time constant	1.51 ms	Encoder system	Encoder IC2048S/R: incremental encoder sin/cos 1 Vpp 2048 S/R with C and D track
		Thermal time constant	35 min		
		Shaft torsional stiffness	37000 Nm/rad		
		Net weight of the motor	9.1 kg		



Figure similar

MLFB-Ordering data

1FK7062-2AC74-1AA0

Optimum operating point

Optimum speed 2000 rpm

Optimum power 1.3 kW

Limiting data

Max. permissible speed (mech.) 7200 rpm

Max. permissible speed (inverter) 3200 rpm

Maximum torque 26.0 Nm

Maximum current 10.9 A

Recommended Motor Module

Rated inverter current 3 A

Maximum inverter current 9 A

Maximum torque 22.90 Nm