



Power semiconductor module 600 V, for 3RW52/50, 470 A

product designation	Power semiconductor module
design of the product	600 V, 470 A
manufacturer's article number	
<ul style="list-style-type: none"> • of soft starter 	3RW5075 (2x), 3RW5076 (2x)
<ul style="list-style-type: none"> • of soft starter 	3RW5146 (3x), 3RW5147 (3x)
<ul style="list-style-type: none"> • of soft starter 	3RW5246 (3x), 3RW5247 (3x)

Ambient conditions	
<ul style="list-style-type: none"> • ambient temperature during storage 	-40 ... +80 °C

Certificates/ approvals	
General Product Approval	Declaration of Conformity



[Miscellaneous](#)



Test Certificates	Marine / Shipping	other
-------------------	-------------------	-------

[Type Test Certificates/Test Report](#)



[Confirmation](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RW5924-0SS05>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RW5924-0SS05>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RW5924-0SS05>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RW5924-0SS05&lang=en

Characteristic: Tripping characteristics, I²t, Let-through current

<https://support.industry.siemens.com/cs/ww/en/ps/3RW5924-0SS05/char>

Characteristic: Installation altitude

<http://www.automation.siemens.com/bilddb/index.aspx?view=Search&mlfb=3RW5924-0SS05&objecttype=14&gridview=view1>

Simulation Tool for Soft Starters (STS)

<https://support.industry.siemens.com/cs/ww/en/view/101494917>

last modified:

10/21/2020 