

MOTION CONNECT 500

MLFB-Ordering data

6FX5002-2CA31-2BA0



Figure similar

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Electrical data

Design of the sensor

Test voltage, rms Signal conductors

500 V

Rated voltage U0/U in accordance with EN 50395 Power conductors

30 V

Mechanical data

Type of connection cable engine side

Type of connection cable converter side

Maximum cable outer diameter

Smallest bending radius (fixed installation)

null

Smallest bending radius (flexible installation)

Number of bends, max.

Maximum traversing velocity

Acceleration horizontal, max

Tensile stress, max. Fixed installation

Tensile stress, max. Flexible installation

Torsional stress

Absolute 30°/m

Length



Figure similar

MLFB-Ordering data

6FX5002-2CA31-2BA0

Technical data

Ambient temperature

Operation with permanently installed cable	-20 ... 80 °C
Operation with moving cable	0 ... 60 °C
Storage	-20 ... 80 °C

Kind of connection cable

Material of the cable sheath	PVC DESINA-Color green RAL 6018
Type of insulation	Without CFC and silicone
Standard for behavior in fire: flame resistance	EN 60332-1-1 to 1-3
Oil resistance	EN 60811-2-1 (mineral oil only)

Verification of suitability as authorisation for USA

Verification of suitability as authorisation for Canada