





Power semiconductor module 480 V, for 3RW55/52, 171 A





Product designation	Power semiconductor module
Design of the product	480 V, 171 A
Manufacturer's article number	
• of soft starter	3RW5136 (3x)
• of soft starter	3RW5236-..C.4 (3x)
• of soft starter	3RW5536-..HA.4 (3x)
Ambient conditions	
Ambient temperature	
• during storage	-40 ... +80 °C
Certificates/ approvals	

General Product Approval	Declaration of Conformity	Test Certificates	Marine / Shipping
 CCC	 EAC	 EG-Konf.	 ABS

[Miscellaneous](#)

[Type Test Certificates/Test Report](#)

Marine / Shipping	other
 LRS	 PRS



[Confirmation](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RW5953-0SM04>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RW5953-0SM04>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RW5953-0SM04>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RW5953-0SM04&lang=en

Characteristic: Tripping characteristics, I_t, Let-through current

<https://support.industry.siemens.com/cs/ww/en/ps/3RW5953-0SM04/char>

Characteristic: Installation altitude

<http://www.automation.siemens.com/bilddb/index.aspx?view=Search&mlfb=3RW5953-0SM04&objecttype=14&gridview=view1>

last modified:

03/03/2020