

Labeling plate 26 mm for PT relay



General technical data	
Display version LED	No
Design of the switching function positively driven	No
Reference code acc. to DIN 40719 extended according to IEC 204-2 acc. to IEC 750	E
Reference code acc. to DIN EN 81346-2	C
Reference code acc. to DIN EN 61346-2	C
Product component Plug-in socket	No
Auxiliary circuit	
Number of NC contacts for auxiliary contacts	0
Number of NO contacts for auxiliary contacts	0
Number of CO contacts	0
• for auxiliary contacts	0
Connections/ Terminals	
Product function	
• removable terminal	No
Installation/ mounting/ dimensions	
Mounting position	any

## Certificates/ approvals

General Product Approval

Declaration of Conformity

other



EG-Konf.

[Miscellaneous](#)

[Confirmation](#)

## Further information

**Information- and Downloadcenter (Catalogs, Brochures,...)**

[www.siemens.com/sirius/catalogs](http://www.siemens.com/sirius/catalogs)

**Industry Mall (Online ordering system)**

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mfb=LZS:PT17040>

**Cax online generator**

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mfb=LZS:PT17040>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/LZS:PT17040>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mfb=LZS:PT17040&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mfb=LZS:PT17040&lang=en)

last modified:

11/20/2019