



Figure similar

## Data sheet for SIMOTICS T-1FW3

Article No. : 1FW3208-1SH72-6AA0

Client order no. :  
Order no. :  
Offer no. :  
Remarks :

Item no. :  
Consignment no. :  
Project :

### Engineering data

	$P_N$ [kW]	$M_N$ [Nm]	$I_N$ [A]	$n_N$ [rpm]	$M_{max}$ [Nm]	$I_{max}$ [A]	$n_{max, inv}$ [rpm]	$M_0$ [Nm]	$I_0$ [A]
ALM 400V	63.0	2,000	153	300	3,700	340	690	2,100	160
ALM 480V	75.0	2,000	153	360	3,700	340	690	2,100	160
SLM 400V	57.0	2,000	153	270	3,700	340	690	2,100	160
SLM 480V	69.0	2,000	153	330	3,700	340	690	2,100	160

### Mechanical data

Motor type	Permanent-magnet synchronous motor
Shaft height	200
Cooling	Water cooling
Vibration severity grade	Grade A
Shaft and flange accuracy	Tolerance N (at normal running temperature)
Degree of protection	IP54
Design acc. to Code I	IM B14
Temperature monitoring	KTY84 temperature sensor in the stator winding
Color	Anthracite grey RAL 7016 (Standard)
Type of the bearing	Normal (Standard)
Shaft extension	Hollow shaft
Encoder system	Resolver, multi-pole (number of pole pairs corresponds to number of pole pairs of the motor)
Encoder mounting system	Belt-mounted
Sound pressure level $L_pA(1m)$ motor rated load, tolerance + 3dB	73 dB <sup>1)</sup>

### Limiting data

Max. permissible speed (mech.)	1,000 rpm
Max. permissible speed (inverter)	690 rpm
Maximum torque	3,700 Nm
Maximum current	340 A

### Physical constants

Thermal time constant	20 min
Moment of inertia	13,100 kgcm <sup>2</sup>
Weight (approx.)	350 kg

### Connection

Type of electrical connection	Terminal box for power cable, connector for encoder signals and temperature sensor
Terminal box position	Transverse left
Power connection	Terminal box top

<sup>1)</sup> at 4 kHz rated pulse frequency at the rated operating point