

Data sheet for SIMOTICS M-1PH8

Article No. : 1PH8186-1AF30-2AC1



Figure similar

Client order no. :

Item no. :

Order no. :

Consignment no. :

Offer no. :

Project :

Remarks :

Engineering data

	P_N [kW]	M_N [Nm]	I_N [A]	U_N [V]	f_N [Hz]	n_N [rpm]	M_{max} [Nm]	I_{max} [A]	n_{max} [rpm]	M_0 [Nm]	I_0 [A]	η	$\cos \varphi$	$I\mu$ [A]	
Y	ALM 400V	125.0	682.0	225.0	385	59.2	1,750	1,230	400.0	5,000.0	682.0	225	0.942	0.88	80.0
	BLM/SLM 400V	108.0	688.0	225.0	330	50.9	1,500	1,230	400.0	5,000.0	688.0	225	0.936	0.89	79.0
	ALM/BLM/SLM 480V	135.0	645.0	210.0	445	67.5	2,000	1,230	400.0	5,000.0	645.0	210	0.948	0.87	83.0

Mechanical data

Motor type	Squirrel cage asynchronous motor
Shaft height	180
Cooling	Open circuit cooling DE-> NDE
Vibration severity grade	A
Shaft and flange accuracy	N
Degree of protection	IP23
Design acc. to Code I	IM B3 (IM B6, IM B7, IM B8, IM V6)
Temperature monitoring	KTY84 temperature sensor in the stator winding
Color	Standard (Anthracite RAL 7016)
Type of the bearing	Standard
Shaft extension	Feather key with half key balancing
Encoder system	Without encoder

Physical constants

Thermal time constant	29 min
Moment of inertia	0.652 kgm ²
Weight (approx.)	422 kg

Connection

Type of electrical connection	Terminal box
Position of the connection	NDE top
Power connection	NDE
Signal connection	right
Terminal box designation	1XB7422-P06

Cooling data and sound pressure level

Airflow, min.	0.21 m ³ /s
Sound pressure level L _{pA} (1m) motor + external fan operation 50 HZ rated load, tolerance + 3dB	73 dB ¹⁾
Air discharge	axial
Pressure drop	450 Pa

¹⁾ at a rated frequency of 2 kHz and a speed range of up to 3000 rpm