

product type designation



Battery housing extension for RTU3000C range with autonomous power supply

Battery expansion enclosure for holding two mono cells. Suitable for SIMATIC RTU3000C family; batteries must be purchased separately and are not included in scope of delivery. Observe note regarding battery type in the Equipment Manual!

electrical data	
number of electrical connections	2
type of electrical connection	Sockets for connecting to SIMATIC RTU3000C and another battery enclosure
mechanical data	
material	Housing: Plastic. Battery holder: Spring steel, nickel-plated
ambient conditions	
ambient temperature	
<ul style="list-style-type: none"> in vertical mounting position / during operation during storage during transport 	-40 ... +60 °C -40 ... +70 °C -40 ... +70 °C
relative humidity	
<ul style="list-style-type: none"> at 30 °C / without condensation / during operation / maximum 	95 %
protection class IP	IP20
design, dimensions and weights	
design	compact
width	45 mm
height	100 mm
depth	75 mm
net weight	125 g
product feature / conformal coating	No
further information / internet-Links	
Internet-Link	
<ul style="list-style-type: none"> to website: TIA Selection Tool to website: Industrial communication to website: Industry Mall to website: Information and Download Center to website: Image database to website: CAx-Download-Manager to website: Industry Online Support 	http://www.siemens.com/tia-selection-tool http://www.siemens.com/simatic-net https://mall.industry.siemens.com http://www.siemens.com/industry/infocenter http://automation.siemens.com/bilddb http://www.siemens.com/cax https://support.industry.siemens.com

last modified:

12/18/2020